


1-Line, Bi-directional, Transient Voltage Suppressor




Features

- " Stand-off voltage: $\pm 12\text{V}$ Max
- " Transient protection for each line according to
IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
IEC61000-4-4 (EFT): 40A (5/50ns)
IEC61000-4-5(surge): 6A (8/20 s)
- " Ultra-low capacitance: $C_J = 5\text{pF}$ typ
- " Low leakage current
- " Low clamping voltage: $V_{CL} = 21.0\text{V}$ typ. @ $I_{PP} = 16\text{A}$ (TLP)
- " Solid-state silicon technology

Mechanical Data

- " Package : DFN1006-2L
- " Terminals : Tin plated leads, solderable per
J-STD-002 and JESD22-B102
- " Polarity: No marking on bi-directional types
- " Marking: cD

Definitions of electrical characteristics



ESDLC12VLB


Maximum Ratings

PARAMETER	SYMBOL	Rating	UNIT
Peak pulse power ($t_p = 8/20 \text{ s}$)	P_{pk}	120	W
Peak pulse current ($t_p = 8/20 \text{ s}$)	I_{PP}	6	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	KV
Junction temperature	T_J	125	$^{\circ}\text{C}$
Operating temperature	T_{OP}	-40~85	$^{\circ}\text{C}$
Storage temperature	T_{STG}	-55~150	$^{\circ}\text{C}$


Electrical Characteristics $\dot{A}T_a=25$ Unless otherwise specified $\dot{A}$

vCharacteristics (Typical)


820 ns waveform per IEC61000-4-5




Clamping voltage vs. Peak pulse current




Non repetitive peak pulse power vs. Pulsetime




Contact discharge current waveform per IEC61000-4-2



Capacitance vs. Reverse voltage



Power derating vs. Ambient temperature




ESDLC12VLB


ESDclamping
(+8kVcontactdischargeper IEC61000-4-2)

ESDclamping
(8kVcontactdischargeper IEC61000-4-2)

TLPMeasurement



vOutline Dimensions



6 \ P E R O	P L Q	P P	0 D
\$			
%			
&			
&			
'			
(			
)			
*			

P P

ESDLC12VLB

vRecommend land pattern (Unit:mm)

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.