





Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, automotive power electronics, soldered on printed circuit boards, soldered on J-STD-002 and JESD22-B102

- **Polarity:** Cathode line denotes the cathode end



■Maximum Ratings (T_a=25 Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS28AQ	SS210AQ
Device marking code			SS28A	SS210A
Repetitive peak reverse voltage	V _{RRM}	V	80	100
Maximum RMS voltage	V _{RMS}	V	56	70
Maximum DC blocking voltage	V _{DC}	V	80	100
Maximum average forward rectified current at T _L (Fig.1)	I _O	A	2.0	
Surge(non-repetitive)forward current @60Hz half-sine wave,1 cycle, T _J =25	I _{FSM}	A	75	
Voltage rate of change (rated V _R)	dV/dt	V/μs	10000	
Storage temperature	T _{stg}		-55 ~+175	
Junction temperature	T _J		-55 ~+175	

■Electrical Characteristics(T_a=25 Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS		TYP	MAX	UNIT
Instantaneous forward voltage	V _F	I _F =2A	T _J =25	0.77	0.8	V
			T _J =125	0.62	0.66	
Reverse current	I _R	Rated V _R	T _J =25	-	1	μA
			T _J =125	20	150	
Typical junction capacitance	C _J	V _R =4V,f=1MHz		60	-	pF
Reverse recovery time	T _{RR}	I _F =1A,di/dt=-50A/μs,V _{RM} =30V		25	-	ns



SS28AQ THRU SS210AQ

■ Thermal Characteristics ($T_a=25$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS28AQ	SS210AQ
Thermal Resistance	$R_{\theta J-A}$	/W	75 ¹⁾	
	$R_{\theta J-L}$		17 ¹⁾	

Note

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Characteristics (Typical)

■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SS28AQ- SS210AQ	F2	Approximate 0.067	7500	120000	13" reel



SS28AQ THRU SS210AQ

■ Outline Dimensions

DO-214AC(SMA)			
Dim	Min	Max	
A	1.25	1.58	
B	2.40	2.83	
C	4.00	4.75	
D	1.90	2.30	
E	4.93	5.28	
F	0.76	1.41	
G	0.05	0.20	
H	0.15	0.31	
I	1.7	2.1	

ΩSuggested Pad Layout

DO	
Dim	Millimeters



SS28AQ THRU SS210AQ

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, lifesaving, lifesustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.