


General Purpose Rectifier

Features

Typical Applications

Mechanical Data

Package



Terminals

Polarity:

Maximum Ratings

PARAMETER	SYMBOL	UNIT	1A1	1A2	1A3	1A4	1A5	1A6	1A7

Electrical Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	1A1	1A2	1A3	1A4	1A5	1A6	1A7

\$ 7+58 \$

v7KHUPDO &KDUDÄFWHUL8VQV FVV RWKHUÄLVH VSHFLILHG

3\$5\$0(7(5	6<0%2/	81,7	\$	\$	\$	\$	\$	\$
7\SLFDO 7KHUPDO	5H5LVWD-QFH							

v2UGHULQJ ,QIRUPPSWLRQ

35() (5(' 3 1	3\$&.\$*(&2' (	81,7 : (, *+7 J	0,1,080 3\$&.\$*(SF	,11(5 %2; 48\$17,7< S	287(5 &\$572 48\$17,7< SF	'(/,9(5< 02' (
\$ a \$	'	\$SSUR[LPDWH	\$SSUR[LPDWH			
\$ a \$	&	\$SSUR[LPDWH	\$SSUR[LPDWH			

1A1 THRU 1A7



Disclaimer
