



Bridge Rectifiers

Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** 4KBJ
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25 Unless otherwise specified

PARAMETER		SYMBOL	UNIT	KBJ1512
Device marking code				KBJ1512
Maximum Repetitive Peak Reverse Voltage		VRRM	V	1200
Maximum RMS Voltage		VRMS	V	840
Maximum DC blocking Voltage		VDC	V	1200
Average Rectified Output Current @60Hz sine wave, R-load	With heatsink T _c =100	I _O	A	15
	Without heatsink T _a =25			3.3
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, T _j =25		I _{FSM}	A	220
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, T _j =25				440
Current squared time @1ms≤t≤8.3ms, T _j =25 , rating of per diode		I ² t	A ² S	201
Storage temperature		T _{stg}		-55 ~ +150
Junction temperature		T _j		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute		V _{dis}	KV	2
Mounting torque @Recommend torque 5kg cm		Tor	kg cm	8


■Electrical Characteristics T_a=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	KBJ1512
Maximum instantaneous forward voltage drop per diode	V _F	V	IFM=7.5A	1.1
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	μA	T _j ≤ V 1%	4



■ Outline Dimensions

4KBJ



Dimensions in millimeters



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herei